



SOPWITH WATCH COMPANY

Messerschmitt Bf 109 Pas-de-Calais

Case

MATERIALS Messerschmitt Bf 109 hardened steel cockpit armor plating Caseback, 316L stainless steel, signed, engraved	DIMENSION Ø 41.00 mm	WATER RESISTANCE Water-resistant to 200 meters
LUG WIDTH 20mm	LUG-TO-LUG 49mm	HARDNESS Titanium carbide coating 1500 HV Enhanced historic steel 168.2 HV
MANUFACTURING Steel processed, melted, poured, cast, laboratory analysis, enhanced to 5360 grade steel at Sopwith Foundry, Houston USA	FINISH Bead blasted finish Titanium carbide physical vapor deposition coating	MAGNETIC FIELD RESISTANCE 20,000 Gauss

Dial & Hands

DIAL 3 piece Double stainless steel stacked Oblique 25-degree bronze 24 hour chapter ring	HANDS Diamond cut steel	BEZEL Bronze 120-position Unidirectional rotating Azimuth +/- 3 degrees Luminous sapphire insert
---	-----------------------------------	--

Movement & Functions

MOVEMENT TYPE Automatic, bidirectional rotor Mecaline Specialities Calibre 2893-A2 Élaboré, ETA SA Manufacture Horlogère Suisse, Grenchen, Switzerland Power reserve, 42 hours Frequency, 28,800 bph 21 jewels	FUNCTIONS Hours, minutes, seconds, GMT, azimuth LUME Swiss multi-layered, Swiss X1 grade Light Old Radium GL	ANTI-SHOCK SYSTEM Jeweled Incabloc SA Novodiac, Durnico steel/brass La Chaux-de-Fonds, Switzerland CROWN Signed, extruded diamond grip bronze, 3.50 x 7.00 mm
---	---	---

Strap

MATERIAL Stitched, hand-cut Horween leather	COLOR Brown	BUCKLE Tang buckle with Sopwith Logo emboss
---	-----------------------	---



SOPWITH WATCH COMPANY

Nieuport 28

Case

MATERIALS

Gnome Monosoupape 9 Type N
Caseback, 316L stainless steel,
signed, engraved
Caseback, 316L stainless steel,
signed, engraved

LUG WIDTH
20mm

DIMENSION

Ø 41.00 mm

LUG-TO-LUG

49mm

WATER RESISTANCE

Water-resistant to 200 meters

HARDNESS

Titanium carbide coating 1500 HV
Enhanced historic steel 168.2 HV

MANUFACTURING

Steel processed, melted, poured, cast,
laboratory analysis, enhanced to 5360
grade steel at Sopwith Foundry,
Houston USA

FINISH

Bead blasted finish Titanium carbide
physical vapor deposition coating

MAGNETIC FIELD RESISTANCE

20,000 Gauss

Dial & Hands

DIAL

3 piece Double stainless steel stacked
Oblique 25-degree bronze 24 hour
chapter ring

HANDS

Diamond cut steel

BEZEL

Bronze 120-position Unidirectional
rotating Azimuth ± 3 degrees
Luminous sapphire insert

Movement & Functions

MOVEMENT TYPE

Automatic, bidirectional rotor Mecaline
Specialities Calibre 2893-A2 Élaboré,
ETA SA Manufacture Horlogère Suisse,
Grenchen, Switzerland Power reserve,
42 hours Frequency, 28,800 bph 21
jewels

FUNCTIONS

Hours, minutes, seconds, GMT,
azimuth

LUME

Swiss multi-layered, Swiss X1 grade
Light Old Radium GL

ANTI-SHOCK SYSTEM

Jeweled Incabloc SA Novodiac, Durnico
steel/brass La Chaux-de-Fonds,
Switzerland

CROWN

Signed, extruded diamond grip bronze,
3.50 x 7.00 mm

Strap

MATERIAL

Stitched, hand-cut Horween leather

COLOR

Brown

BUCKLE

Tang buckle with Sopwith Logo emboss



SOPWITH WATCH COMPANY

Thomas-Morse Scout

Case

MATERIALS Thomas Morse S4C Scout Le Rhone 9C steel pistons Caseback, 316L stainless steel, signed, engraved Caseback, 316L stainless steel, signed, engraved	DIMENSION Ø 41.00 mm	WATER RESISTANCE Water-resistant to 200 meters
LUG WIDTH 20mm	LUG-TO-LUG 49mm	HARDNESS Titanium carbide coating 1500 HV Enhanced historic steel 168.2HV
MANUFACTURING Steel processed, melted, poured, cast, laboratory analysis, enhanced to 5360 grade steel at Sopwith Foundry, Houston USA	FINISH Bead blasted finish Titanium carbide physical vapor deposition coating	MAGNETIC FIELD RESISTANCE 20,000 Gauss

Dial & Hands

DIAL 3 piece Double stainless steel stacked Oblique 25-degree bronze 24 hour chapter ring	HANDS Diamond cut steel	BEZEL Bronze 120-position Unidirectional rotating Azimuth +/- 3 degrees Luminous sapphire insert
---	-----------------------------------	--

Movement & Functions

MOVEMENT TYPE Automatic, bidirectional rotor Mecaline Specialities Calibre 2893-A2 Élaboré, ETA SA Manufacture Horlogère Suisse, Grenchen, Switzerland Power reserve, 42 hours Frequency, 28,800 bph 21 jewels	FUNCTIONS Hours, minutes, seconds, GMT, azimuth LUME Swiss multi-layered, Swiss X1 grade Light Old Radium GL	ANTI-SHOCK SYSTEM Jeweled Incabloc SA Novodiac, Durnico steel/brass La Chaux-de-Fonds, Switzerland CROWN Signed, extruded diamond grip bronze, 3.50 x 7.00 mm
---	---	---

Strap

MATERIAL Stitched, hand-cut Horween leather	COLOR Brown	BUCKLE Tang buckle with Sopwith Logo emboss
---	-----------------------	---



SOPWITH WATCH COMPANY

Focke-Wulf Fw 190 Tunisian Desert

Case

MATERIALS

Focke-Wulf Fw 190 hardened steel cockpit armor plating Caseback, 316L stainless steel, signed, engraved Caseback, 316L stainless steel, signed, engraved

LUG WIDTH
20mm

DIMENSION

Ø 41.00 mm

LUG-TO-LUG

49mm

WATER RESISTANCE

Water-resistant to 200 meters

HARDNESS

Titanium carbide coating 1500 HV
Enhanced historic steel 168.2 HV

MANUFACTURING

Steel processed, melted, poured, cast, laboratory analysis, enhanced to 5360 grade steel at Sopwith Foundry, Houston USA

FINISH

Bead blasted finish Titanium carbide physical vapor deposition coating

MAGNETIC FIELD RESISTANCE

20,000 Gauss

Dial & Hands

DIAL

3 piece Double stainless steel stacked Oblique 25-degree bronze 24 hour chapter ring

HANDS

Diamond cut steel

BEZEL

Bronze 120-position Unidirectional rotating Azimuth ± 3 degrees
Luminous sapphire insert

Movement & Functions

MOVEMENT TYPE

Automatic, bidirectional rotor Mecaline Specialities Calibre 2893-A2 Élaboré, ETA SA Manufacture Horlogère Suisse, Grenchen, Switzerland Power reserve, 42 hours Frequency, 28,800 bph 21 jewels

FUNCTIONS

Hours, minutes, seconds, GMT, azimuth

LUME

Swiss multi-layered, Swiss X1 grade Light Old Radium GL

ANTI-SHOCK SYSTEM

Jeweled Incabloc SA Novodiac, Durnico steel/brass La Chaux-de-Fonds, Switzerland

CROWN

Signed, extruded diamond grip bronze, 3.50 x 7.00 mm

Strap

MATERIAL

Stitched, hand-cut Horween leather

COLOR

Brown

BUCKLE

Tang buckle with Sopwith Logo emboss



SOPWITH WATCH COMPANY

Focke-Wulf Fw 190 Arctic Sea

Case

MATERIALS Focke-Wulf Fw 190 hardened steel cockpit armor plating Caseback, 316L stainless steel, signed, engraved Caseback, 316L stainless steel, signed, engraved	DIMENSION Ø 41.00 mm	WATER RESISTANCE Water-resistant to 200 meters
LUG WIDTH 20mm	LUG-TO-LUG 49mm	HARDNESS Titanium carbide coating 1500 HV Enhanced historic steel 168.2 HV
MANUFACTURING Steel processed, melted, poured, cast, laboratory analysis, enhanced to 5360 grade steel at Sopwith Foundry, Houston USA	FINISH Bead blasted finish Titanium carbide physical vapor deposition coating	MAGNETIC FIELD RESISTANCE 20,000 Gauss

Dial & Hands

DIAL 3 piece Double stainless steel stacked Oblique 25-degree bronze 24 hour chapter ring	HANDS Diamond cut steel	BEZEL Bronze 120-position Unidirectional rotating Azimuth +/- 3 degrees Luminous sapphire insert
---	-----------------------------------	---

Movement & Functions

MOVEMENT TYPE Automatic, bidirectional rotor Mecaline Specialities Calibre 2893-A2 Élaboré, ETA SA Manufacture Horlogère Suisse, Grenchen, Switzerland Power reserve, 42 hours Frequency, 28,800 bph 21 jewels	FUNCTIONS Hours, minutes, seconds, GMT, azimuth LUME Swiss multi-layered, Swiss X1 grade Light Old Radium GL	ANTI-SHOCK SYSTEM Jeweled Incabloc SA Novodiac, Durnico steel/brass La Chaux-de-Fonds, Switzerland CROWN Signed, extruded diamond grip bronze, 3.50 x 7.00 mm
--	---	--

Strap

MATERIAL Stitched, hand-cut Horween leather	COLOR Brown	BUCKLE Tang buckle with Sopwith Logo emboss
---	-----------------------	---



SOPWITH WATCH COMPANY

Focke-Wulf Fw 190 Baltic Winter

Case

MATERIALS

Focke-Wulf Fw 190 hardened steel cockpit armor plating Caseback, 316L stainless steel, signed, engraved Caseback, 316L stainless steel, signed, engraved

LUG WIDTH
20mm

DIMENSION

Ø 41.00 mm

LUG-TO-LUG

49mm

WATER RESISTANCE

Water-resistant to 200 meters

HARDNESS

Titanium carbide coating 1500 HV
Enhanced historic steel 168.2 HV

MANUFACTURING

Steel processed, melted, poured, cast, laboratory analysis, enhanced to 5360 grade steel at Sopwith Foundry, Houston USA

FINISH

Bead blasted finish Titanium carbide physical vapor deposition coating

MAGNETIC FIELD RESISTANCE

20,000 Gauss

Dial & Hands

DIAL

3 piece Double stainless steel stacked Oblique 25-degree bronze 24 hour chapter ring

HANDS

Diamond cut steel

BEZEL

Bronze 120-position Unidirectional rotating Azimuth +/- 3 degrees
Luminous sapphire insert

Movement & Functions

MOVEMENT TYPE

Automatic, bidirectional rotor Mecaline Specialities Calibre 2893-A2 Élaboré, ETA SA Manufacture Horlogère Suisse, Grenchen, Switzerland Power reserve, 42 hours Frequency, 28,800 bph 21 jewels

FUNCTIONS

Hours, minutes, seconds, GMT, azimuth

LUME

Swiss multi-layered, Swiss X1 grade Light Old Radium GL

ANTI-SHOCK SYSTEM

Jeweled Incabloc SA Novodiac, Durnico steel/brass La Chaux-de-Fonds, Switzerland

CROWN

Signed, extruded diamond grip bronze, 3.50 x 7.00 mm

Strap

MATERIAL

Stitched, hand-cut Horween leather

COLOR

Brown

BUCKLE

Tang buckle with Sopwith Logo emboss